



NOTES:

ELECTRICAL:

- 1. VOLTAGE RATING : 125V AC RMS
- 2. CURRENT RATING : 1.5A mp
- 3. CONTACT RESISTANCE : 100 MILLI OHMS MAX
- 4. INSULATION RESISTANCE : 1000M OHMS MIN @ 500V DC
- 5. DIELECTRIC STRENGTH : 750V AC RMS 60Hz, 1MIN
- 6. CAT. 6a PERMANENT LINK : CONFORM TO ANSI/TIA/EIA-568 C. 2

ENVIRONMENTAL:

ISO/IEC 11801:2010 CLASS EA

- 1. STORAGE : -40° TO+85°
- 2. OPERATION : 0° TO+70°

RJ45 JACK COMPLY TO REQUIREMENTS OF IEC-60603-7-5
MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68

MECHANICAL

- 1. SHIELD MATERIAL BRASS C2680 T=0.25MM
- 2. HOUSING MATERIAL PBT+15%GF
- 3. CONTACT MATERIAL PHOSHOR BRONZE PLATING GOLD
- 4. PANEL FRAME ZN PLATING
- 5. IDC MATERIAL: PC TERMINAL:PHOSPHOR BRONZE, TIN PLATING
- 6. RJ45 JACK LIFE: 750 TIMES MIN
- 7. IDC LIFE : 200 TIMES MIN
- 8. RETENTIVENESS OF INSERTION STRUCTURE: 50N 60±5s

Accessory:

- 1. Cable Tie(75×1.9mm) ×24Pcs
 - 2. Instruction Sheet
 - 3. Screw and Nut M6*18mm x 4set
- RoHS2.0 & REACH COMPLIANT

UNO ITEM NO.	Colour
90ITBPP6AG	Gray RAL 7035
90ITBPP6AS	Black RAL 9005

Productname:

19" Patchpanel - geschirmt - CAT 6A -
24 Port - PoE + fähig - 1 HE

MATERIAL LIST:

⑦	Bottom Panel	1.5mm thickness Metall Panel with plastic powder cladding Frosting surface treatment	1	
⑥	Upper Panel Cover	1.0mm thickness Metall Panel with plastic powder cladding Frosting surface treatment	1	
⑤	RJ45 Jack	Housing-Fireproof PBT Pin-8P8C gold plated	24	
④	PCB	1.6mm UL-94V0	3	
③	IDC Body	PC/ABS /With Colour Coded Printing T568A/B	24	
②	IDC Pin	Phosphor Bronze & Tinned	192	
①	IDC Terminal	For 22-24 AWG Cable	24	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK