



NOTES:

ELECTRICAL:

- 1. VOLTAGE RATING : 125V AC RMS
- 2. CURRENT RATING : 1.5A mp
- 3. CONTACT RESISTANCE : 100 MILLI OHMS MAX
- 4. INSULATION RESISTANCE : 1000M OHMS MIN @ 500V DC
- 5. DIELECTRIC STRENGTH : 750V AC RMS 60Hz, 1MIN
- 6. CAT. 6a PERMANENT LINK : CONFORM TO ANSI/TIA/EIA-568 C.2-1

ENVIRONMENTAL:

- 1. STORAGE : -40° TO+85°
- 2. OPERATION : 0° TO+70°

RJ45 JACK COMPLY TO REQUIREMENTS OF IEC-60603-7-5
 MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68

MECHANICAL

- 1. SHIELD MATERIAL BRASS C2680 T=0.25MM
- 2. HOUSING MATERIAL PBT+15%GF
- 3. CONTACT MATERIAL PHOSHOR BRONZE PLATING GOLD
- 4. IDC MATERIAL: PC WHITE TERMINAL:PHOSPHOR BRONZE, TIN PLATING
- 5. RJ45 JACK LIFE: 750 TIMES MIN
- 6. IDN LIFE : 200 TIMES MIN
- 7. RETENTIVENESS OF INSERTION STRUCTURE: 50N 60^{±5s}

Accessory:

- 1. Cable Tie(75×3.0mm) ×24Pcs
- 2. Instruction Sheet
- 3. Screw and Nut M6*18mm x 4set

RoHS2.0 and REACH COMPLAINT

UNO ITEM NO.	Colour
90LNPP6ASSG	Gray RAL 7035
90LNPP6ASSS	Black RAL 9005

Productname:

Business Patchpanel - geschirmt -
 CAT 6A - 24 Port - 1 HE - POE + fähig -
 mit integrierten Staubschutz

MATERIAL LIST:

NO.	PARTS NAME	SPECIFICATION STANDARD	QT'Y	REMARK
⑧	Bottom Panel	1.5mm thickness Metallic Panel with plastic powder cladding Frosting surface treatment	1	
⑦	Upper Panel Cover	1.2mm thickness Metallic Panel with plastic powder cladding Frosting surface treatment	1	
⑥	Dust cap	Automatic shutdown, Surface plating, Silver	24	
⑤	RJ45 Jack	Housing-Fireproof PBT Pin-8P8C gold plated	24	
④	PCB	1.6mm	3	
③	IDC Body	PC WHITE/With Colour Coded Printing T568A/B	24	
②	IDC Pin	Phosphor Bronze & Tinned	192	
①	IDC Terminal	For 22-24 AWG Cable	24	



Lidsteiner Straße 81a
 D - 65232 Taunusstein

Telefon: +49 (0) 6128 48 955 - 0
 Telefax: +49 (0) 6128 48 955 -20

Internet: www.LIEBERNETZ.de
 E-Mail: info@LIEBERNETZ.de